

### With screw-fastened lid

**Material:**  
Stainless steel 1.4301 (AISI 304)

**Surface finish:**  
Brushed, grain 240

**Protection category:**  
IP 66 to EN 60 529/09.2000

**Supply includes:**  
Enclosure, lid with all-round foamed-in PU seal.

**Certificates:**  
PTB 03 ATEX 1013U

### With hinged door

**Material:**  
Stainless steel 1.4301 (AISI 304)  
Mounting plate: Sheet steel

**Surface finish:**  
Brushed, grain 240  
Mounting plate: Zinc-plated

**Protection category:**  
IP 66 to EN 60 529/09.2000

**Supply includes:**  
Enclosure, door with all-round foamed-in PU seal, mounting plate.

**Certificates:**  
PTB 02 ATEX 1082U

**Approvals,**  
see page 41.

**Detailed drawing,**  
see page 1226/1227.

### With screw-fastened lid

Width (B1) mm	Packs of	150	200	300	300	300	400	Page
Height (H1) mm		150	200	150	200	300	200	
Depth mm		80	80	80	80	120	120	
<b>Model No. KEL</b>	<b>1</b>	<b>9301.000</b>	<b>9303.000</b>	<b>9302.000</b>	<b>9304.000</b>	<b>9306.000</b>	<b>9305.000</b>	
Weight (kg)		1.3	1.8	1.8	2.4	3.9	3.6	

### Accessories


Mounting plates		1560.700	1562.700	1561.700	1563.700	1567.700	1564.700	978
-----------------	--	----------	----------	----------	----------	----------	----------	-----

To order Ex enclosures in stainless steel 1.4404 (AISI 316L), please add extension .500 to the Model No. Delivery times available on request.

### With hinged door

Width (B1) mm	Packs of	200	300	380	380	380	600	600	760	800
Height (H1) mm		300	380	300	380	600	600	760	760	1000
Depth mm		155	210	155	210	210	210	210	300	300
Mounting plate width (F1) mm		162	334	334	334	334	549	549	704	739
Mounting plate height (G1) mm		275	275	275	355	570	570	730	730	955
<b>Model No. KEL</b>	<b>1</b>	<b>9401.600</b>	<b>9409.600</b>	<b>9402.600</b>	<b>9403.600</b>	<b>9404.600</b>	<b>9405.600</b>	<b>9406.600</b>	<b>9407.600</b>	<b>9408.600</b>
Number of cams		1	1	1	1	2	2	2	2	2
Weight (kg)		3.8	7.7	7.4	9.7	13.3	15.6	22.3	30.5	36.3

To order Ex enclosures in stainless steel 1.4404 (AISI 316L), please add extension .500 to the Model No. Delivery times available on request.



**Support rails**  
in matching sizes,  
Model No. see page 1002.



**Wall mounting bracket,**  
Model No. see page 975.